

Date of Deposit: August 31, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Assistant Commissioner For Patents, Washington, D.C. 20231

By: Benjamin Trella

JC922 U.S. PTO



08/31/00

Attorney's Docket No. XER 2 0330
D/99421

UTILITY PATENT APPLICATION TRANSMITTAL LETTER

(Only for nonprovisional applications under 37 CFR 1.53(b))

Assistant Commissioner for Patents
Washington, D.C. 20231

Transmitted herewith for filing in the patent application of:

Gaurav Sharma and Shen-ge Wang

Entitled: **SHOW-THROUGH WATERMARKING OF DUPLEX PRINTED DOCUMENTS**

Enclosed are:

- [XX] 12 sheets of specification, 3 sheets of claims, 1 sheet of Abstract.
[XX] 10 sheets of drawings, Figures 1 - 9.
[XX] an assignment of an invention to XEROX CORPORATION (and transmittal therefor).
[XX] a Declaration and Power of Attorney for Patent Application.

CLAIMS AS FILED

FOR	NO. FILED	NO. EXTRA	RATE	FEE
TOTAL CLAIMS	18 - 20 =	-0-	[XX] \$18 LARGE [] \$09 SMALL	\$ -0-
INDEPENDENT CLAIMS	4 - 3 =	1	[XX] \$78 LARGE [] \$39 SMALL	\$ 78.00
BASIC FEE	[XX] LARGE ENTITY	\$690	[] SMALL ENTITY	\$345
TOTAL FILING FEES 768.00				

☒ Please charge Deposit Account No. 24-0037 in the amount of \$ 768.00.

☒ The Commissioner is hereby authorized to charge any additional fees which may be required at any time during the prosecution of this application without specific authorization, or credit any overpayment to Deposit Account No. 24-0037.

☐ A check in the amount of \$ _____ to cover the filing fee is enclosed.

Date

8/31/00

Patrick R. Roche
Attorney of Record
Patrick R. Roche
Reg. No. 29,580
FAY, SHARPE, FAGAN,
MINNICH & MCKEE, LLP
1100 Superior Avenue
Seventh Floor
Cleveland, Ohio 44114-2518
(216) 861-5582

SHOW-THROUGH WATERMARKING OF DUPLEX PRINTED DOCUMENTS

Field of the Invention

5 The subject invention relates to the art of image/text printing, and is especially applicable to a method and apparatus wherein duplex printing (printing the front and back sides of a document) is implemented in a manner for forming a visible watermark upon show-through illumination of the document. The watermark results from halftone pattern interaction between the front and back images on the document,
10 but is invisible upon mere front-lit illumination of either of the sides.

Background of the Invention

Conventional watermarks, such as are produced by the pressure of a projecting design, as in the mold, during the manufacturing process of paper are well
15 known. The watermark can be seen when the paper is held up and back-lit by show-through illumination. The watermark is intended not to be visible when the paper is not held up, e.g., at rest on a desk and front-lit by incident illumination. Watermarks are useful for authentication purposes or identification of an origin or author of the resident document.

20 Much of the printing in today's business and scientific world is accomplished electronically, such as with digital color printer engines, which inherently provide only a limited number of output possibilities due to their binary nature, i.e., they produce either a dot or no dot at a given pixel location. Pressure formed watermarks can only be incorporated into the original paper stock in such
25 printers and cannot be inserted at the time of printing.

30 The well known notion of halftoning (representing a continuous tone image with a binary representation) can produce an image including rapidly varying spatial patterns normally not visible to a human visual system, but artifacts thereof can be, especially those generated by interaction between adjacent or overlaying printing patterns.

design process is disclosed in US Patents No. 5,734,752 to Knox and No. 5,790,703 to Wang.

A system utilizing halftone outputs produced by stochastically clustered pixel screens, referred to as "stoclustic" screens (U.S. Patent No. 5,859,955 to Wang) combines the advantages of both cluster halftone and stochastic halftone screens. The use of stoclustic halftone screens for watermarking of images through the use of suitable halftones is also known and disclosed in related U.S. application Serial No. 09/069,095 to Wang and is incorporated herein by reference as it discloses a particular clustered-dot screen design method useful in implementation of the subject invention, as will be more fully explained below. But this method requires that the watermark detection is performed by either electronic scanning and image processing of the printed image or by overlaying a distinct transparency on a printed image containing the watermark for effectively interacting the distinct screen transparency with the printed image. Watermark identification requiring scanning and additional image processing or via a separate transparency document is inconvenient and undesirable. Such problems are intended to be overcome by the present invention.

Duplex printing is fairly common for increased paper use efficiency, and for the subject invention is exploited for the selective interaction of images on both sides of the document to effectively achieve an overlaying of patterns forming a desired watermark upon show-through illumination.

Brief Summary of the Invention

In accordance with the present invention, a method and apparatus is provided for duplex printing of a document for forming a show-through watermark thereon upon back-lit illumination. The front pattern is printed on the front side of a document and the back pattern is printed on the back side of the document. The front and back patterns are disposed for interacting in back-lit illumination to produce a recognizable marking, wherein the marking is not visible upon only front-lit illumination.

In accordance with another aspect of the present invention, either one or both of the front and back patterns are adjusted for forming the intended

interacting, and the adjustment primarily comprises at least one of phase, frequency or angle shifting of halftone dots. The patterns preferably comprise clustered-dot halftone screens, though others methods of screen-based or screen-less halftoning could also be used.

5 In accordance with yet another limited aspect of the present invention, when the shifting comprises a phase shift, the shifting of the phase of the halftone screen for either one or both of the front and back images comprises a shift embedded in the screen. The watermark comprises significant local variation in brightness resulting in a pattern clearly visible to the human eye.

10 In accordance with yet another aspect of the present invention, when the shifting comprises a shifting in angle of frequency, the watermark comprises a moiré pattern.

One advantage of the present invention is a method and apparatus for forming a watermark in a merely electronically printed document.

15 Another advantage of the subject invention is the formation of the watermark in a duplex printing process without severe registration requirements between front and back images on the document.

20 Yet another advantage of the subject invention is the formation of the watermark through a variety of alternative interaction effects between the images such as phase, angle or frequency shifting.

Yet another advantage of the subject invention is the formation of a recognizable marking in an electronically printed document suitable for authenticating or identifying the document.

25 Other advantages and benefits of the present invention will become apparent to those of ordinary skill in the art upon a reading and understanding of the following detailed description of the preferred embodiments.

Brief Description of the Drawings

30 The invention may take form in various components and arrangements of components. The drawings are only for purposes of illustrating the preferred embodiments and are not to be construed as limiting the invention. Where:

FIGURE 1 is a cross-sectional view of a document having the printed images on the front and back sides of the document;

FIGURES 2a – 2c show a particular halftone pattern and alternative overlap patterns thereof;

FIGURES 3a – 3c show halftone patterns wherein the phase of the pattern of FIG. 3b is shifted from FIG. 3a and wherein FIG. 3c shows a consequence of overlapping the patterns of FIGS. 3a and 3b;

FIGURE 4 illustrates an exemplary watermark of the kind that can be generated by the subject invention;

FIGURE 5 shows a composed stoclustic screen capable of generating the watermark shown in Fig. 4;

FIGURES 6a-6c are diagrammatic illustrations approximating how watermarks formed in accordance with the present invention would appear upon show-through illumination;

FIGURES 7 and 8 are alternative flowcharts of the steps for forming a watermark in a duplex printing operation in accordance with the present invention; and,

FIGURE 9 is an apparatus for duplex printing of documents.

Detailed Description of the Preferred Embodiments

Referring now to the drawings wherein the showings are for purposes of illustrating preferred embodiments of the invention only and not for limiting same, the invention describes a way of halftoning a duplex printed document for forming a show-through watermark visible from the document upon back-lit illumination. For a duplex printed document, the images are printed on both the front and back sides of the document and these images are effectively overlaid if the document is held up and viewed in a show-through mode with a light on the back of the page.

Fig. 1 graphically illustrates a show-through illumination for document 10 having a transmittance T_p and having a printed image on side one $T_1(x,y)$ comprised of halftone cells 12, 14, 16 and another image on side two, $T_2(x,y)$ comprised of cells 18, 20. A mathematical representation of the image seen upon show-through illumination is $I(x,y)T_1(x,y)T_pT_2(x,y)$, wherein the illumination is

represented by $I(x,y)$, and $T_1(x,y)$ and $T_2(x,y)$ represent the transmittances of the images printed on side one and side two, respectively. Viewing the document with back-lit illumination thus results in the multiplicative combination of the images printed on the front and the back-side. The present invention embeds a distinct visible pattern in this show-through image by designing the halftone images printed on the two sides such that their multiplicative combination results in a visible artifact corresponding to the distinct visible pattern.

In the following description, it will be assumed that the halftone output is black and white and the illumination profile $I(x,y)$ is uniform and given by a constant value I . It should be recognized that these assumptions are introduced for clarity of description and are not intended to limit the scope of the invention. The invention is just as applicable to the printing of color images and is especially intended for such applications in accordance with the same halftoning patterns as are herein described for black and white.

For ideal black and white halftone images, the image transmittances $T_1(x,y)$ and $T_2(x,y)$ are binary functions taking the value 0 over regions where dots are printed (indicating no light is transmitted) and 1 where no dots are printed (indicating all light is transmitted). The image seen in show-through, i.e., $I T_1(x,y) T_2(x,y)$ (Fig. 1) therefore takes the value 0 at pixel locations where there is printing on at least one side (because at least one of $T_1(x,y)$ or $T_2(x,y)$ is zero) and a value $I T_p$ in regions where there is no printing on either side. Consequently, the image seen in show-through is lighter at pixel locations on the page with no printing on either side in comparison to pixel locations that have printing on at least one side. In actual practice, the halftone transmission profile is not ideal and there is spreading of light in paper, however, the qualitative characteristics of the above description still hold.

Consider the case when the halftone patterns to be printed on both sides are identical and correspond to a 50% area coverage in a checkerboard pattern as shown in Fig. 2a. If the halftone patterns printed on the two sides are exactly in phase, i.e., the printed and the non-printed regions of the checker-boards on the two sides are exactly aligned, the image seen in show-through is also a checker-board image which is dark in the region with printing on both sides and light in the region with no printing on either side, as shown in Figure 2b. If the halftone patterns printed

on the two sides are completely out of phase, i.e., the printed regions of the checker-boards on either side are exactly aligned with the unprinted regions on the other side, the image seen in show-through is dark throughout, as shown in Figure 2c. Therefore, if the halftone patterns on the two sides are perfectly out of phase, the average image
5 (which is what the eye perceives) seen in show-through appears darker in comparison to the case when the halftone patterns on the two sides are perfectly in phase. For intermediate phase alignment, the average image also takes on an intermediate value between the two extremes of exact phase agreement and complete phase disagreement.

10 It is a feature of the subject invention that the halftone patterns printed on the two sides are generated so as to have a spatially varying phase difference between the front and the back side patterns which generates a recognizable artifact upon back-lit illumination in the form of a local variation in the brightness of the show-through image. The artifact is configured in a readily identifiable form as a
15 watermark.

A spatial variation in the phase agreement between the front and back side halftone patterns can be introduced by adjusting the phase of either the front-side, or the back-side halftone or both halftones. For most current day printers, the registration between the front and back side images is usually poor over the extent of
20 the document due to non-uniformities in the printing process (nonlinearity in the motion of the laser used in the printer for writing the pixels onto paper, non-uniform paper motion, etc.) It is therefore beneficial to incorporate the variation in phase in the halftone pattern on a single side keeping the phase on the other side relatively constant (apart from any slow variations due to the effects mentioned earlier).

25 Incorporation of the phase variation in a single side makes the method robust to any mis-registration errors between the two sides.

It is a principal feature of the subject invention, as will be noted below, that the use of clustered-dot halftone screens for back side and front side imaging particularly facilitates the formation of the watermark through a phase variation
30 embedded in the halftone pattern on one side. The watermark, or other hidden information, formed by overlaying screens in show-through is based on cluster-to-

cluster correlation and is much easier to visibly detect than pixel-to-pixel correlation which is confounded by the spreading of light in paper.

Stochastic halftone screens (as described in US Patent No. 5,859,955 to Wang) provide the freedom to locate clustered print dots "arbitrarily". This feature enables the creation of clustered-dot halftone screens that can embed of local phase shifts.

Figs. 3a and 3b show halftone patterns where Fig. 3a is a checkerboard pattern created by a regular 45-degree cluster halftone screen. Fig. 3b is similar to Fig. 3a with four slightly stretched columns 30, 32, 34, 36 in the middle portion of the Figure. Due to pitch difference of the two patterns in the respective Figures, the phase measuring the transition between white and black cells is changed from in phase (0 shift) on the left portions 40, 42 to the opposite phases (180° shift) on the right in the last columns 44, 46.

When the halftone patterns of Figs. 3a and 3b are overlapped together, a rather easily recognizable high contrast between the left and right portions of the figure is formed as shown in Fig. 3c. In other words, it can be seen that the left portion 48 of Fig. 3c is easily identifiable as much lighter in color portion than the right portion 50.

As described earlier, when halftones are printed on both sides of a page and viewed with back-lit illumination, the overlaying of the patterns on the front and back sides is automatically accomplished. So, if one-side of a duplex printed page has a halftone pattern with almost no spatial phase variation and the other side's halftone pattern incorporates a spatial phase-shift in the halftone pattern from 0° to say X°, the phase-difference between the sides will also go through a X° change over the spatial region with the phase shift. This variation in phase-difference will produce a distinct visible artifact in the form of a spatial variation in the brightness. If X=360, i.e., the halftone pattern goes through a complete phase-cycle, the phase difference between the halftone patterns on the two sides will also go through a complete cycle and result in a brightness variation covering the full range possible, with the brightness being the highest where the phase-difference between the halftone-patterns on the two sides is zero, and the lowest where the phase difference between the two sides is 180°. The

choice of the phase shift amount X may involve additional considerations such as non-perceptibility of the resulting shifts in halftone images.

In order to obtain a watermark in a given shape, a clustered halftone screen incorporating a phase shift is created. A watermark in the shape of a letter T can be created by a phase shifting adjustment in the halftone screen as shown in Fig. 4, where the complete screen includes a sub-region in the shape of T over which the screen has a phase shift of 180° in relation to the background. In particular, the area 60 ambient to the distinct visible pattern (i.e., "T") has zero phase shift. A transition region 62 surrounds the T region and is also in the shape of a T, over which the phase shift is gradually introduced so as to avoid the introduction of visible artifacts in the image due to a sudden phase shift. A full phase shift region 64 (i.e., 180° phase shift) clearly forms the intended variable pattern. The screen incorporating the phase shift may be designed directly or may be composed of phase-shift halftone tiles that are composed together to produce the overall screen. Fig. 5 shows a composed stoclastic screen for forming the T watermark of Fig. 4 wherein the solid lines indicate the contour of phase tiles having a phase zero, and the dash lines, the contour of phase 180° . The individual halftone tiles may be obtained for example, by using the methods disclosed in pending US Patent application Serial No. 09/069,095. What the actual result of this example, when printed in duplex mode and viewed under back-lighting, would then appear like to an operator is approximated in Fig. 6a.

In order to insert the halftone into a duplex printed page, one side of the page is printed using the above-described phase shift halftone screen and the other side is printed using a halftone screen with no phase shift. When the document is held up for show-through viewing (with a backlight), the phase shift over the transition region will show-up as a variation in brightness of the show-through image, thereby making the outline of the T visible as the watermark.

The phase difference between the halftone patterns on the front and the back side in the non-phase shifted region of the watermark bearing screen is referred to as the "native phase-difference". The exact nature of the visible watermark pattern depends on this native phase-difference. This dependence variation is illustrated in Figures 6a, 6b and 6c, which represent the visible watermark seen for native phase-differences of 0° , 180° , and 90° , respectively. If the native phase difference is zero

(Fig. 6a), the watermark is visible as a dark T with a lighter surrounding region, because the halftones on the two sides are completely in phase over the background and completely out of phase over the T. Likewise, if the native phase difference is 180° (Fig. 6b), the watermark is visible as a light T, surrounded by a relatively dark surrounding region. If the native phase difference is 90° (Fig. 6c), the inside of the T and the outside have the same brightness but the watermark is still visible as the outline of the T corresponding to the brightness variation produced in the phase change region. For intermediate values of the native phase difference, the visible watermark lies somewhere between these three extremes.

If good registration between the front and the back sides can be achieved, one can control the appearance of the watermark to correspond to any of the above-mentioned three extremes or any intermediate appearance by adjusting the native phase difference. This can be accomplished for instance by a simple shift of the halftone screen. If reasonably good registration of the front and back sides is not possible, the native phase difference may take any value between 0° and 180° and produce a corresponding visible watermark pattern. Note, however, that the watermark is always visually distinguishable even with no control of the registration of the front and back side printing.

It is an important feature of the invention that when either side of the document (Fig. 1) is viewed only the halftone gray image printed on that side is seen and no watermark is apparent. However, when the page is held against the light and viewed, the T of Fig. 4 is visible over the portion of the image where the phase shift watermark is embedded in the screen.

With reference to Fig. 7, a block diagram/flowchart for the subject invention embodiment is illustrated. An intended watermark pattern 70 is predetermined which will result in an interaction causing a distinct visible pattern corresponding to the watermark. Accordingly, front and back side halftone screens must be designed 72 which, when overlapped, will cause the pattern. The screens thus must be different, and in accordance with the preferred embodiment, will embed a phase shift as in the example discussed above. Halftone screen one 74 and halftone screen two 76 are imparted to a controller wherein a front side image 76 is printed 84 on a first side of the document in accordance with halftoning pattern 78. The back

side of the document is printed **84** with the back side image **80** in accordance with halftoning **82** so that the duplex printed document forms the show-through watermark.

Fig. 8 shows an alternative flowchart wherein the front and back side images **76**, **80** are predetermined and the halftoning of the front side and back sides **86**, **88**, is determined in consideration of the watermark pattern **70**. The result of the printing on two sides **84** is the same. Note that the watermark pattern may be used to influence the halftoning process for either one side or both sides, either directly in the halftoning process or through incorporation in the halftone screen.

With reference to Fig. 9, duplex printers **90** are well known and the apparatus disclosed in the Figure is discussed in much greater detail in other U.S. patents as, for example, Patent Nos. 4,960,272 or 5,313,253. A decision gate **92** may divert successive copy sheets to duplex inverter roll **94** or onto a transport path to finishing station **96**. When gate **92** diverts the sheet onto inverter roll **94**, roll **94** inverts and stacks the sheets to be duplexed in duplex tray **96**. Tray **96** provides an intermediate or buffer storage for those sheets that have been printed on one side and on which an image that will be subsequently printed on the second, on both sides thereof, i.e., the sheets being duplexed. The simplex sheets in tray **96** are fed, in seriatim, by bottom feeder **98** from tray **96** for transfer of the toner powder image to both sides of the copy sheets.

The area of interaction between the front and back side images which is most susceptible to proper formation of an intended watermark preferably comprises areas of a constant mid-level gray. Since the watermark is embedded in the halftone screen, there are typically multiple repetitions of the watermark over the printed page. Thus, if the intended watermark viewed in the show-through illumination tends to get masked by other image details in the regions where the images on one or both sides are rapidly varying, a repetitive pattern of the watermark hopefully can still form a visible portion in the regions in which the image is relatively uniform, such as the sky or water. If an image is to be printed only on one side of the sheet, a mid-level gray pattern may be printed on the other side to produce the show-through watermark. The show-through watermark can also be produced by printing overlapping constant mid-level gray patches on the two sides, where front-lit viewing of either side shows only a mid-level gray patch.

The invention has been described above, with reference to a specific embodiment based on phase shift clustered-dot screens. Alternate embodiments of the invention are possible. In particular, the watermark may be embedded in the screen as a spatial variation in halftone frequency or angle. In addition, the variation of phase, frequency or angle may be used with other halftoning methods that may or may not use a screen. Where the adjustment of the halftoning screen is other than phase shift, such as frequency or angle shifting, the watermark is visible as moiré between the screens on the front and back side. An objective of developing either an angle or frequency shifting watermark is to develop one without visible artifacts in front side illumination of either of the front or back side images.

The invention is described with reference to the preferred embodiments. Obviously, modifications and alterations will occur to others upon the reading and understanding of the proceeding detailed description. It is intended that the invention be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

Having thus described the invention, we now claim:

1. A method of generating a show-through pattern on a duplex-printed document through selective disposition of halftone patterns on opposite sides of the document comprising steps of:

printing a first image on a first side of the document in a first halftone pattern; and,

printing a second image on a second side of the document in a second halftone pattern wherein the first and second halftone patterns are disposed to form a recognizable marking distinct from the first and second images upon illumination from a show-through light source.

2. The method as described in claim 1 wherein the said recognizable marking is produced through a local phase shift of printed halftone dots.

3. The method as defined in claim 2 wherein the first and second halftone patterns are obtained by utilizing a first and a second clustered halftone screen of substantially the same halftone-dot frequency wherein the second halftone screen incorporates a phase shift in dot pattern in the shape of the said recognizable marking.

4. The method as claimed in claim 3 wherein the phase shift in the second halftone screen comprises a shift of 180° over the embedded watermark pattern.

5. The method as defined in claim 4 wherein the watermark comprises significant local variation in brightness resulting in a pattern clearly visible to the human eye.

6. The method described in claim 1 wherein the said recognizable marking is produced through a local frequency shift of the printed halftone dots.

7. The method as defined in claim 6 wherein the first and second halftone patterns are obtained by utilizing a first and a second clustered-dot halftone screen and the second halftone screen incorporates a frequency shift in dot pattern in the shape of the said recognizable marking.

8. The method as defined in claim 7 wherein the recognizable marking comprises a variation in moirée pattern.

9. The method described in claim 1 wherein the said recognizable marking is produced through a local angle shift of printed halftone dots.

10. the method as defined in claim 1 wherein the printings comprise a color printing.

11. A duplex-printed document having a show-through watermark comprising a selective overlay between a first image on a first side of the document and a second image on a second side of the document wherein the images comprise halftone dots relatively adjusted for forming the watermark upon illumination from a show-through light source.

12. The document as claimed in claim 11 wherein the watermark is produced through a local phase shift of the halftone dots between the first and second sides of the document.

13. The document as claimed in claim 11 wherein the second image adjustment comprises angle or frequency shifting between the first and second images.

14. A printing apparatus for duplex printing a document having a show-through watermark comprising first and second images on opposed sides of the document wherein the images comprise halftone dot patterns for forming an associated overlay pattern between the first and second images, resulting in a

recognizable pattern comprising the watermark, upon illumination by a show-through light source, and wherein the watermark is unrecognizable from either images alone upon illumination by a front light source.

5 15. The printing apparatus as defined in claim 11 wherein the halftone dots are relatively shifted by at least one of phase, angle or frequency.

10 16. The printing apparatus as defined in claim 11 wherein the watermark is primarily recognizable in a reasonably large and relatively uniform area of overlap between the first and second images.

15 17. A method of duplex printing a document for forming a show-through watermark thereon upon back-lit illumination comprising steps of:
 printing a front pattern on a front side of the document; and,
 printing a back pattern on a back side of the document disposed for
interacting with the front pattern in the back-lit illumination to produce a recognizable marking, wherein the marking is not recognizable upon only front-lit illumination.

20 18. The method as claimed in claim 17 wherein the interacting comprises at least one of phase, frequency or angle shifting of halftone dot patterns

SHOW-THROUGH WATERMARKING OF DUPLEX PRINTED DOCUMENTS

ABSTRACT


5 A printing apparatus and method for duplex printing a document
having a show-through watermark wherein the watermark is comprised of first and
second images on both sides of the document. The images comprise stoclustic
halftone screens having a substantially common registration wherein the second
image is relatively shifted from the first image for forming an associated overlay
10 pattern between the first and second images resulting in a recognizable pattern
comprising the watermark upon illumination by a show-through light source. The
watermark is unrecognizable from either image alone upon illumination from a front
light source. The relative shifting can be implemented by either phase, frequency or
angle shifting between the front and back side images.

$$\text{Image Seen in Showthrough} = I(x,y)F_1(x,y)T_p F_2(x,y)$$

Fig 1




Fig 2a



F1936




Fig 3c



a

Figure 2. Fifty-percent area coverage checker-board pattern



b

Figure 2b. Show-through image for exact phase agreement of printed checkerboards on both sides.



c

Figure 2c. Show-through image for complete phase disagreement of printed checkerboards on both sides.

001620.162296
0662291.083100




FIG 4

05552291.083100


[illegible]

Fig 5




FIG. 6a

FIG. 6b

001580.1622569





FIG. 6c



F19 7




FIG 8.

0062221.003403

09-06-2007 08:04 AM




FIG. 8

Attorney Docket No. XER 2 0330

D/99421

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SHOW-THROUGH WATERMARKING OF DUPLEX PRINTED DOCUMENTS

the specification of which

XX is attached hereto OR was filed on
Application Serial No.
and was amended on (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application(s) for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

_____ (Number)	_____ (Country)	_____ (Filing Date)
-------------------	--------------------	------------------------

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Prior Provisional U.S. Patent Application(s):

_____ (Application Serial No.)	_____ (Filing Date)
-----------------------------------	------------------------

I hereby claim the benefit under Title 35, United States, Section 120 of any United States application(s) or any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information which is material to patentability as defined in Title 37, of Federal Regulations Code, Section 1.56(a) which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U.S. Patent Application(s):

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status) (patented, pending, abandoned)
-----------------------------------	------------------------	---

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Steven M. Auvil	Reg. No. 40,492	Mark E. Bandy,	Reg. No. 35,788
Brian G. Bembenick	Reg. No. 41,463	John P. Cornely,	Reg. No. 41,687
Joseph D. Dreher,	Reg. No. 37,123	Christopher B. Fagan,	Reg. No. 22,987
Jude A. Fry,	Reg. No. 38,340	Steven M. Haas,	Reg. No. 37,841
W. Scott Harders,	Reg. No. 42,629	Michael E. Hadzinski,	Reg. No. 34,185
Richard M. Klein,	Reg. No. 33,000	Thomas E. Kocovsky, Jr.,	Reg. No. 28,383
Sandra M. Koenig,	Reg. No. 33,722	Brian E. Kondas,	Reg. No. 40,685
Scott A. McCollister,	Reg. No. 33,961	James W. McKee,	Reg. No. 26,482
Richard J. Minnich,	Reg. No. 24,175	Jay F. Moldovanyi,	Reg. No. 29,678
Philip J. Moy,	Reg. No. 31,280	Timothy E. Nauman,	Reg. No. 32,283
Patrick R. Roche,	Reg. No. 29,580	Albert P. Sharpe, III,	Reg. No. 19,879
R. Scott Speroff,	Reg. No. 37,450	Mark S. Svat,	Reg. No. 34,261
John E. Beck	Reg. No. 22,833	Richard B. Domingo	Reg. No. 36,784
Henry Fleischer	Reg. No. 25,582	Mark Costello	Reg. No. 31,342
Eugene O. Palazzo	Reg. No. 20,881		

SEND CORRESPONDENCE TO:

Albert P. Sharpe, III, Esq.

Fay, Sharpe, Fagan, Minnich & McKee, LLP

1100 Superior Avenue, 7th Floor

Cleveland, Ohio 44114-2518

DIRECT TELEPHONE CALLS TO:

(name and telephone number)

Albert P. Sharpe, III
(216) 861-5582

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under Section 1001 of Title 18 of the United States code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of sole or first joint inventor: **GAURAV SHARMA**

Inventor's Signature: Gaurav Sharma

Date: Aug 31, 2000

Residence: Webster, New York 14580

Country of Citizenship: India

Post Office Address:

3 Woodrose Drive
Webster, NY 14580

Full name of second joint inventor: **SHEN-GE WANG**

Inventor's Signature: Shen-Ge Wang

Date: 8/31/00

Residence: Fairport, New York 14450

Country of Citizenship: U.S.A.

Post Office Address:

9 Shelborne Chase
Fairport, NY 14450

00000001.000100